



Physical, Performance and Regulatory Properties

Performance Properties	EnTron-AE
Boiling Point	160° F / 71° C
Flash Point, ASTM D-93	None
Evaporation Rate (n Butyl Acetate = 1)	4.5
Azeotropic Composition	Yes
Inhibited Against Metal Corrosion	Yes
Inhibited Against Hydrolysis	Yes
Kauri Butanol Value	129
Non-Volatile Residue, max.	10 ppm
Water Content, max.	150 ppm

Technical Physical Properties	
Specific Gravity, 25/25°C	1.33
Specific Heat, 25°C, cal/g	0.27
Latent Heat, cal/g	58.5
Viscosity, 25°C, cps	0.49
Vapor Pressure, 25°C (mm Hg)	139
Vapor Density (Air =1)	4.3
Water Solubility (g/100 ml)	0.25
Flammability Limits LEL/UEL	3% - 9.0%
Acid Acceptance, as NaOH, wt% min.	0.25
Alkalinity, as NaOH, wt % max.	0.02
Hansen Parameters: Non-Polar / Polar	17.9 / 5.8

Environmental, Regulatory, and Health Profile	
Global Warming Potential (GWP)	.00005
Ozone Depletion Potential (ODP)	0.016
Volatile Organic Compound (VOC)	Yes
Hazardous Air Pollutant	Yes
Transportation	Regulated
ASTM D6368-06	Base Material Conforms
Iso Propyl Bromide Content, max.	Meets ASTM D6368-06
Manufacturer's Workplace Exposure Guideline	See SDS

