

# ULTRA<sup>TM</sup> 250

## ULTRA 250 VS. B250R



- **Compact Foot-Print: fits standard 30" door**
- **Digital temperature readouts**
- **On casters for mobility**
- **Easy maintenance**
- **Refrigerated for excellent solvent containment**
- *Optional 250W ultrasonics*
- *Optional Spray Wand*
- *Optional 120V Plug*

**Reliance**

Specialty Products, Inc.  
847.640.8923

FEATURE	ULTRA 250	BRANSON 250R
Ultrasonic Tank Size	11"L x 9"W x 8"D 792 sq. in.	11"L x 8"W x 6"D 528 sq. in.
Vapor Zone	18"L x 11"W x 8"D	16"L x 11"W x 6"D
Overall Dimensions	36"L x 24"W x 44"H	26"L x 16"W x 46"H
Refrigerated Solvent Containment	Yes	Yes
Ultrasonic Filtration	Yes, Optional	No
Ultrasonics	250 Watts standard Adjustable power & sweep Field replaceable	100 Watts Not Adjustable. Not field replaceable
Spray Wand System	Yes, Optional	Yes, Optional
Heat	Electric—screw in heaters for easy removal	Heat pad glued to underside of tank— Not field replaceable
Safety Controls	Adjustable Safety Controls display set point & temp and Safety Low Level Float	Not adjustable No temperature display
Control Panel Indicators	Comprehensive Indicator Lights for status of system conditions.	Minimal Indicator Lights
Control Panel Components	Off-The-Shelf Components Easy to get	Proprietary Board— hard to fix and replace
Lid	Manual Horizontal Slide	Lift off Lid
Freeboard Ratio	100%	75%
Electrical Service	208V or 240V /1 PH or 120V PLUG	208V or 240V /1 PH only
Solvent Fill	5.6 Gallons	5 Gallons
<b>RELSPEC.COM</b>		