

Model 2012LE Narrow

Ultrasonic & Spray Vapor Degreasing System w/*Optional* Automated Basket Handling System

Ultrasonic Dip Cleaning Tank	20"L x 12"W x 15" Deep
Vapor Cleaning Zone	40"L x 12"W x 12" Deep
Boil Tank	20"L x 12"W
Footprint Dimensions (without casters)	84"Long x 30"W ide x 47" High
FEATURES	
Ultrasonic Cleaning	500 or 1000 Watts of Power at 40
	kHz. Field replaceable components
	Adjustable Power and Sweep.
Vapor Cleaning Spray Cleaning	Vapor Cleaning Zone above
	Boil Tank and Ultrasonic Tank
	Hand Spray Wand and
	Large Spray Reserve Tank
Filtration of Liquid Dip Tank	Continuous Filtration
Boil Tank Access Door	"Easy Ring" Door System
Liquid Dip Tank Access Door	"Easy Ring" Door System
SOLVENT CONTAINMENT	
NESHAP Compliant Features	Yes
Primary Condensing Coil	Refrigerated Stainless Steel
Low-Temp Freeboard	Refrigerated Finned Stainless Steel
Condensation Coil	operating at -10F to -20F
Freeboard Ratio	120%
Horizontal Slide Lid	Manual or Automated
Watlow Solvent Safety and	HTC, LTC, SVC, VU, RT and
Temperature Controls	Low-Level Float
Monitoring Vapor Degreaser's	Comprehensive Indicator Light
Correct Operating Condition	System and Temperature Displays
AUTOMATED PART CLEANING	
Automated Basket Handling System	Yes—Optional
	Yes—Optional
Automated Basket Handling System	Yes—Optional 25 Gallons

VaporDegreasingEquipment.com

Reliance Specialty Products, Inc. Please 855 Morse Ave. Elk Grove Village, IL 60007 phone: 847.640.8923 Fax: 47.640.8974

Please Call for a Price Quote (847) 640-8923

©Reliance Specialty Products, Inc. 2011-2018

- Fits through standard door way
- Process Parts at Ground Level
- Easy maintenance
- Spray wand for additional cleaning
- Excellent Solvent Containment & NESHAP Compliant
- Reduced Solvent & Operating Costs
- On Casters for mobility
- Compatible with variety of solvents
- 120% Freeboard

Manufactured in the USA by:





State-of-the-Art Cleaning



Foot Activated Spray Lance System



Primary & Sub-Zero Coils running standard refrigerant



Simple Control Safety Panel



Specialty Products, Inc.

855 Morse Ave. Elk Grove Village, IL 60007 Phone: 847.640.8923 Fax: 847.640.8974

ULTRA 2012LE (Narrow) Features

- **NESHAP COMPLIANT** Vapor Degreasing System
- Fits through standard 30" door
- Solid Stainless Steel Construction Heavy Gauge 304 Stainless Steel used on tank, water separator, spray reserve tank, primary coil, low-temperature coil, lid system, tank access doors and tank fittings.
- Stainless Steel Primary Condensing Coil New Copeland refrigeration system operating with standard R134A refrigerant.
- Sub-Zero Temperature Condensing Coil—Finned stainless steel condensation coil with Copeland R404A refrigeration operating to approximately -20F thus broadening the height of the solvent flash-off dwell zone for enhanced solvent containment.
- Foot Activated Spray Lance System Mag-drive pump with distillate spray reservoir with "Vapor Up Safety Control" which requires presence of vapor to permit operation of spray wand.
- High Volume Condensate Water Separator feeding spray reservoir
- Digital Display Safety Control Panel— including HTC, LTC, SVC, VU, RT
- Ultrasonic Power 500 or 1000 Watts @ 40 kHz field replaceable submersible transducers and plug in external ultrasonic generator for easy servicing
- Ultrasonic Power— Input adjustment & sweep frequency adjustment
- Ultrasonic Immersion Sump filtration and recirculation system with mag-drive pump
- WATLOW Temperature Safety Limit Controls –Digital display on Control Panel; temperature set point as well as actual temperature – SVC (Safety Vapor Control), HTC (High Temperature Control), LTC (Liquid Temperature Control) and RT (Refrigeration Temperature Control)
- Low-Level Float Safety System—Ensures the minimum amount of solvent in boil sump for proper system operation.
- **Comprehensive Indicator Light System on Control Panel** Includes solvent low level float fault indicator lights (for easy identification of operating fault conditions). "Spray Ready" indicator light and zero coil "Defrost" indicator light, illuminated on/off switches for easy identification of system condition "Heat", "Filtration", Main Power", "Refrigeration" and "Low-Temp Refrigeration".
- Horizontal Slide Lid—for solvent containment. Optional power roll-top available.
- **Casters**—for easy movement.
- Simple In & Out Electric Immersion Heater—"Screw-In" Type Elements for easy replacement.
- **Two Sump Access Clean-Out Doors** Boil Sump & Immersion Sump access for ease of maintenance though the clean-out door rather than over the tank top
- One (1) stainless steel workbasket
- Comprehensive 1-Year Manufacturer's Warranty
- ULTRA 2012LE N Operator's Manual

VaporDegreasingEquipment.com

(847) 640-8923

©Reliance Specialty Products, Inc. 2011-2018



State-of-the-Art Cleaning Performance

ULTRA 2012LE-N Benefits

- Simple engineering and stoutness of design for durability and ease-of-maintenance
- Excellent training— start-up, shut down, maintenance and good solvent cleaning work practices
- Easy to support in the field with accessible heating elements, clear temperature read-outs, sophisticated indicator light system, and updated refrigeration systems using standard refrigerant
- Cost effective operation and maintenance
- Compact footprint
- Effective with a variety of non-flammable solvents, including chlorinated, brominated & fluorinated
- State-of-the-art engineering based on a best practices for simplicity, field supportability and reliability
- Minimal Solvent Emissions & Reduced Operating Costs due to NESHAP compliant coils



Narrow width of 30" fits through standard doorway

Options

- Electric horizontal slide lid
- Additional baskets
- Solvent Containment Spill Tray
- Increased Ultrasonic Power
- Choice of vapor degreasing solvent including EnTron, EnTron-Aero, GenTech & AeroTron
- Automated Vertical Basket Handling System



Process parts at ground level.

VaporDegreasingEquipment.com



Please Call For a Price Quote (847) 640-8923

855 Morse Ave. Elk Grove Village, IL 60007 Phone: 847.640.8923 Fax: 847.640.8974



Eliance Vapor Degreasing & Solvent **Cleaning Experts**

(847) 640-8923

ULTRA 2012LE-N: Compatible with

Non-Flammable Solvents

- Simple Change over The ULTRA 2012LE is engineered to be compatible with a variety of solvents and in most cases a simple clean out and change of temperature settings is all that is required.
- 120% Freeboard-helps with vapor containment-so using chlorinated solvents like TCE, TCA, MCL and PERC is still possible.
- Sub-Zero refrigeration coil—in addition to the primary refrigeration system, makes using brominated solvents like GenTech, EnTron & EnTron-Aero or fluorinated solvents such as AeroTron an economical alternative.
- Manual or Automated Slide-Lid—provides additional solvent containment for the new generation of fluorinated solvents like AeroTron and helps reduce evaporation.



nPB Solvent for General **Metal Finishing**





Fluorinated Solvent for Precision Vapor Degreasing

Benefits of Working with Reliance: Manufacture of Solvents & Equipment





Reliance Specialty Products, Inc. 855 Morse Ave. Elk Grove Village, IL 60007 Phone: 847.640.8923 • Fax: 847.640.8974

- Comprehensive Vapor Degreasing Solution Provider Reliance is the only industry player that manufactures both vapor degreasing solvent and vapor degreasing equipment. Our vapor degreasing equipment manufacturing expertise combined with our years of working with a variety of solvent cleaning processes make us able to support our customers in a variety of practical ways.
- Years of experience. A unique history of developing solvents and manufacturing vapor degreasing equipment for precision aerospace, electronics and optics customers.

VaporDegreasingEquipment.com

©Reliance Specialty Products, Inc. 2011-2018